






Picture	Model	Power	Luminaire Efficacy	Lumen output	Input Voltage	LED Brand	Driver Brand	Optics	CCT	SPD	Rating	Lifetime (L ₇₀)	
 1 Module	ZGSM-LD40H4	40W	130lm/w	5200lm	100-277Vac	Philips 3030	Meanwell	TypeI,II,III,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>100,000H	
	ZGSM-LD50H5	50W	125lm/w	6250lm	100-277Vac	Philips 3030	Meanwell	TypeI,II,III,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>100,000H	
	ZGSM-LD60H6	60W	120lm/w	7200lm	100-277Vac	Philips 3030	Meanwell	TypeI,II,III,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>80,000H	
 2 Modules	ZGSM-LD80H4	80W	130lm/w	10400lm	100-277Vac	Philips 3030	Meanwell	TypeI,II,III,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>100,000H	
	ZGSM-LD100H5	100W	125lm/w	12500lm	100-277Vac	Philips 3030	Meanwell	TypeI,II,III,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>100,000H	
	ZGSM-LD120H6	120W	120lm/w	14400lm	100-277Vac	Philips 3030	Meanwell	TypeI,II,III,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>80,000H	
 3 Modules	ZGSM-LD120H4	120W	130lm/w	15600lm	100-277Vac	Philips 3030	Meanwell	TypeI,II,III,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>100,000H	
	ZGSM-LD150H5	150W	125lm/w	18750lm	100-277Vac	Philips 3030	Meanwell	TypeI,II,III,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>100,000H	
	ZGSM-LD180H6	180W	120lm/w	21600lm	100-277Vac	Philips 3030	Meanwell	TypeI,II,III,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>80,000H	
 4 Modules	ZGSM-LD160H4	160W	130lm/w	20800lm	100-277Vac	Philips 3030	Meanwell	TypeI,II,III,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>100,000H	
	ZGSM-LD200H5	200W	125lm/w	25000lm	100-277Vac	Philips 3030	Meanwell	TypeI,II,III,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>100,000H	
	ZGSM-LD240H6	240W	120lm/w	28800lm	100-277Vac	Philips 3030	Meanwell	TypeI,II,III,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>80,000H	
 5 Modules	ZGSM-LD200H4	200W	130lm/w	26000lm	100-277Vac	Philips 3030	Meanwell	TypeI,II,III,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>100,000H	
	ZGSM-LD240H5	240W	125lm/w	30000lm	100-277Vac	Philips 3030	Meanwell	TypeI,II,III,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>100,000H	



Number of Modules	1	2	3	4	5
Packing Size (mm)	480x370x200	555x370x200	630x370x200	705x370x200	780x370x200
Gross Weight (kg)	6.3	7.3	8.6	9.6	10.6

