






LED Street Light - Series H **【5050 Version】**

Picture	Model	Power	Luminaire Efficacy	Lumen output	Input Voltage	LED Brand	Driver Brand	Optics	CCT	SPD	Rating	Lifetime (L ₇₀)
 1 Module	ZGSM-LD40H4	40W	160lm/w	6400lm	100-277Vac	Philips 5050	Meanwell	TypeII,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>85,000H
	ZGSM-LD50H5	50W	155lm/w	7750lm	100-277Vac	Philips 5050	Meanwell	TypeII,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>85,000H
	ZGSM-LD60H6	60W	155lm/w	9300lm	100-277Vac	Philips 5050	Meanwell	TypeII,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>80,000H
 2 Modules	ZGSM-LD80H4	80W	165lm/w	13200lm	100-277Vac	Philips 5050	Meanwell	TypeII,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>85,000H
	ZGSM-LD100H5	100W	160lm/w	16000lm	100-277Vac	Philips 5050	Meanwell	TypeII,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>85,000H
	ZGSM-LD120H6	120W	155lm/w	18600lm	100-277Vac	Philips 5050	Meanwell	TypeII,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>80,000H
 3 Modules	ZGSM-LD120H4	120W	165lm/w	19800lm	100-277Vac	Philips 5050	Meanwell	TypeII,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>85,000H
	ZGSM-LD150H5	150W	160lm/w	24000lm	100-277Vac	Philips 5050	Meanwell	TypeII,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>85,000H
	ZGSM-LD180H6	180W	155lm/w	27900lm	100-277Vac	Philips 5050	Meanwell	TypeII,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>80,000H
 4 Modules	ZGSM-LD160H4	160W	165lm/w	26400lm	100-277Vac	Philips 5050	Meanwell	TypeII,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>85,000H
	ZGSM-LD200H5	200W	160lm/w	32000lm	100-277Vac	Philips 5050	Meanwell	TypeII,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>85,000H
	ZGSM-LD240H6	240W	155lm/w	37200lm	100-277Vac	Philips 5050	Meanwell	TypeII,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>80,000H
 5 Modules	ZGSM-LD200H4	200W	165lm/w	33000lm	100-277Vac	Philips 5050	Meanwell	TypeII,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>85,000H
	ZGSM-LD240H5	240W	160lm/w	38400lm	100-277Vac	Philips 5050	Meanwell	TypeII,V	4000/5000/5700K	10KV	ClassI IP66 IK10	>85,000H

Number of Modules	1	2	3	4	5
Packing Size (mm)	480x370x200	555x370x200	630x370x200	705x370x200	780x370x200
Gross Weight (kg)	6.3	7.3	8.6	9.6	10.6

